

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A battery state-of-charge estimator comprising:
 - a voltage detector unit which detects a voltage of a battery;
 - an internal resistance estimator unit which estimates an internal resistance of the battery;
 - an estimated charging/discharging current calculator unit which calculates an estimated charging/discharging current of the battery based on the internal resistance of the battery determined by the internal resistance estimator unit, the voltage of the battery, and an open voltage of the battery;
 - an SOC estimator unit which estimates a state of charge SOC of the battery based on the estimated charging/discharging current determined by the estimated charging/discharging current calculator unit; [[and]]
 - an open voltage calculator unit which sets the detected voltage of the battery as the open voltage of the battery at an initial calculation of the charging/discharging current and, after the initial calculation, calculates the open voltage of the battery based on the SOC which is previously estimated, and
 - a current detection abnormality detector unit which compares the measured charging/discharging current value which is detected by the current detector which detects the charging/discharging current of the battery and the estimated charging/discharging current value which is determined by one of the estimated charging/discharging current calculator unit, the first charging/discharging current calculator unit, and the second charging/discharging current calculator unit, and determines that the current detector unit is abnormal when a difference between the current values is greater than a predetermined difference and that the current detector unit is normal when the difference is a predetermined value or smaller,

wherein the estimated charging/discharging current calculator unit, a first charging/discharging current calculator unit, or a second charging/discharging current calculator unit calculates the estimated charging/discharging current of the battery based on the internal resistance of the battery, the voltage of the battery, the open voltage of the battery, and a polarization voltage, and

wherein the SOC is estimated based on the estimated charging/discharging current value when the current detection abnormality detector unit determines that the current detector unit is abnormal and the SOC is estimated using the measured charging/discharging current value when the current detection abnormality detector unit determines that the current detector unit is normal.

2.-9. (Canceled).

10. (Previously Presented) A battery state-of-charge estimator according to Claim 1, wherein SOC estimator unit periodically estimates the SOC at a predetermined interval.

11. (Previously Presented) A battery state-of-charge estimator according to Claim 1, further comprising:

a current detector unit which detects a charging/discharging current of the battery;
a first battery full-capacity calculator unit which determines a full capacity of the battery based on the SOC which is estimated by the SOC estimator unit and an integrated value of the charging/discharging current of the battery which is detected by the current detector unit during the estimation of the SOC; and

a second SOC estimator unit which estimates a state of charge of the battery based on the full capacity of the battery which is obtained by the first battery full-capacity calculator unit and the measured charging/discharging current of the battery which is detected by the current detector unit.

12. (Previously Presented) A battery state-of-charge estimator according to Claim 11, further comprising:

a second battery full-capacity calculator unit which determines a full capacity of the battery based on the SOC which is estimated by the first SOC estimator unit or the second SOC estimator unit and an integrated value of the charging/discharging current of the battery which is detected by the current detector unit during the estimation of the SOC, and

a second SOC estimator unit which estimates a state of charge of the battery based on the full capacity of the battery which is obtained by the second battery full-capacity calculator unit and the measured charging/discharging current of the battery which is detected by the current detector unit.

13. (Previously Presented) A battery state-of-charge estimator according to Claim 11, further comprising:

a remaining capacity detector unit which detects a remaining capacity of each individual cell within the battery; and

a remaining energy calculator unit which detects a minimum remaining capacity based on the remaining capacity of each individual cell which is obtained from the remaining capacity detector unit and calculates an amount of remaining energy of the battery based on the minimum remaining capacity.

14-15. (Canceled).

16. (Currently Amended) A battery state-of-charge estimator according to ~~Claim 14~~ Claim 1, wherein

in consideration of on an environmental temperature of the battery, one of the measured charging/discharging current value which is detected by the current detector unit which detects

the charging/discharging current of the battery and the estimated charging/discharging current value which is determined by one of the estimated charging/discharging current calculator unit, the first charging/discharging current calculator unit, and the second charging/discharging current unit is selected and

the SOC is estimated based on the selected charging/discharging current value.

17. (Currently Amended) A battery state-of-charge estimator according to ~~Claim 14~~ Claim 1, further comprising:

a charging/discharging prohibiting unit which prohibits charging and discharging of the battery when the charging/discharging current of the battery considering the polarization voltage exceeds a predetermined value.

18. (Previously Presented) A battery state-of-charge estimator according to Claim 11, wherein

the temperature detector unit is placed in the battery, on a surface of the battery, or near the surface of the battery.

19. (Previously Presented) A battery state-of-charge estimator according to Claim 11, wherein

at least one of the SOC estimator unit, the second SOC estimator unit, and a third SOC estimator unit periodically estimates the SOC at a predetermined interval.